

### DESCRIZIONE - DESCRIPTION

Testa termostatica con sensore a liquido  
 Thermostatic head with liquid sensor  
 Tête thermostatique avec capteur liquide  
 Thermostatische Heizkörperventile



P. Max 10 bar                      Carico lavoro 80 N  
 T. Max 110°C                      Power force value 80 N

### CARATTERISTICHE - FEATURES

- |  |         |  |         |
|--|---------|--|---------|
| • Tempo di risposta<br>Response time<br>Temps de réponse<br>Antwortzeit  | 25 min  | • Isteresi, Hysteresis,<br>Hystérésis, Hysteresis  | 0.6 K   |
| • Influenza della pressione differenziale<br>Differential pressure influence<br>Influence de la pression différentielle<br>Einfluss auf Differenzdruck | 0.50 K  | • Influenza della temp. dell'acqua<br>Water temperature influence<br>Influence de la temp. du fluide<br>Durchgang temperatur einfluß | 0.60 K  |
| • Max pressione differenziale<br>Max differential pressure<br>Pression différentielle max<br>Differenzdruck max  | 1.0 bar | • Portata nominale<br>Nominal flow rate<br>Debit<br>Druckfluß  | 190 l/h |

### DIMENSIONI PRINCIPALI - LEADING DIMENSIONS

