

DESCRIZIONE - DESCRIPTION

Valvola a sfera a passaggio totale con cappuccio piombabile, antilegionella 010-025 c/premistoppa.

Anti-legionella full way ball valve 010-025 with brass locking cap, with stuffing box.




1800


1810

CARATTERISTICHE - FEATURES

- corpo, manicotto cappuccio e sfera in CW617N.
- premistoppa e asta in CW614N.
- sfera lavorata con utensile in diamante, cromata.
- sedi in P.T.F.E. vergine dimensionate con angolo di tenuta di 8° min.
- guarnizione tenuta asta: O-ring+anello in PTFE.
- finitura superficiale sabbiata nichelata, filettature gialle.
- filettature ISO 228/1
- temp. -20° +130°C
- *brass CW617N body end connection cap and ball.*
- *brass CW614N stuffing box and stem.*
- *ball ground by diamond-tipped tool, chromium plated.*
- *virgin P.T.F.E. seats with 8° min. tightness angle.*
- *stem tightness: O-ring + PTFE ring.*
- *nickel plated finishing with yellow threads.*
- *threading to ISO 228/1.*
- *temp. -20° + 130°C*

DIMENSIONI PRINCIPALI - LEADING DIMENSIONS


R	3/8	1/2	3/4	1	1 ¼	1 ½	2
D	20	20	20	23	23	26	26
H	38	38	42	52	61	69	77
L	45	47.5	55	66	80	91	106
M	12	12	12	14	16	17	19
F	10	15	20	25	32	40	50



R	3/8	1/2	3/4	1	1 ¼	1 ½	2
D	20	20	20	23	23	26	26
H	38	38	42	52	61	69	77
L	45.5	48	56	65.5	80	91	107
M1	12	12	12	14	16	17	18.5
F	10	15	20	25	32	40	50

PRESSIONI DI ESERCIZIO A MAX 80°C - WORKING PREASSURES AT 80°C

PN 30	*	*	*	*	*	*	*	p.s.i. 435
	3/8"	1/2"	3/4"	1"	1 ¼"	1 ½"	2"	

PERDITE DI CARICO - PRESSURE DROPS

R"	3/8	1/2	3/4	1	1 ¼	1 ½	2
Kv	9	15	30	57.5	94	160	265

$$\Delta P [\text{mm H}_2\text{O}] = 10.000 \times \left[\frac{G [\text{mc/h}]}{Kv} \right]^2$$